

### Skid-mounted Ozone Generator **GQO-G500**



Ozone Output:	400-500g/hr@80Lpm O2
Ozone Generating Method:	Corona Discharge
Electrical:	220V/50Hz, MAX 4500W
Gas Source Input:	Connect external gas source, oxygen or dry air
Control:	Programmable electronic loop controller
Inlet & Outlet Connection:	1/2" inner thread PVC connection
Application Range:	6000-10000 m3 (Air Disinfection)
Case:	Powder coated Metal Box
Dimension(LxWxH):	29.6" *28.8" *73.3" (750*730*1860 mm)
Net Weight:	- kg

The GQO-G series of BEYOK skid-mounted ozone generators can mix ozone into water to destroy bacteria, purify air and eliminate peculiar smell. They are suitable for food factory assembly lines, restaurants, and refrigerated storages, etc. Connect to the external oxygen source will provide a higher concentration of ozone.

#### Features:

- Skid-mounted
- Simple operation
- High efficiency
- High concentration
- Work continuously
- Economical and low running cost
- Oxygen or dry air feed
- Long working life

#### Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

#### Application:

- Sterilization and disinfection: restaurant, hospital, packing workshop, food factory.
- Food fresh keeping: refrigerated storage.
- Deodorization: basement, garage, store room, hotel, central air-conditioning cooling tower.

#### Size View:

