

Ozone Generator Cell FQ-220



BEYOK
OZONE OZONE

Ozone Output:	160-240 mg/hr @ air
Pump Output:	2-3 L/min, >10 Kpa
Ozone Generating Method	Corona Discharge
Electrical:	AC220V-AC110V-AC24V-DC12V, 6W
Ozone Outlet Connection:	Φ 6mm pagoda joint
Case:	Plastic
Accessory:	Hose +Air stone (Optional)
Dimension(LxWxH):	5"*2.8"*1.5"(128*72*38 mm)
Installation Dimension(LxW):	3.5" *3.2" (90*80 mm)
Net Weight:	- kg

The FQ-series of BEYOK ozone generator cells use ozone core discharge of invention patent, including the integration design of ozone generator tube, ozone driving circuit and air pump, they can provide stable and efficient ozone output, easy to install and maintain.

Features:

- Invention patent ZL200410079317.5
- Integrated design three in one unit with driving circuit, ozone generator tube and air pump
- Stable & efficient output
- Low noise
- Long working life

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Washing machine, dishwasher, water machine, water purification machines, coin-operated sale water, fruit and vegetable detoxification machines, aquatic animals, the spa machine, surfing bathtub, slimmer.
- Medical equipment, air purifier, disinfection cabinet, refrigerator, dryer, shoe ark, wardrobe, beauty equipment, oxygen machine, toilet, incubator, car.

Size View:

