

Ozone Generator Cell **FQ-300F**



| | |
|------------------------------|--------------------------------|
| Ozone Output: | 300-400 mg/hr @ air |
| Pump Output: | 2-3 L/min, >10 KPa |
| Ozone Generating Method: | Corona Discharge |
| Electrical: | AC220V-AC110V-AC24V-DC12V, 10W |
| Ozone Outlet Connection: | Φ 6mm pagoda joint |
| Case: | Plastic |
| Accessory: | Hose +Air stone (Optional) |
| Dimension(LxWxH): | 5.6"*3.9"*1.7"(143*99*43 mm) |
| Installation Dimension(LxW): | 6.0"*1.6" (152*40 mm) |
| Net Weight: | 1.1lbs (0.5 kg) |

BEYOK OZONE GOZONE

The FQ-series of BEYOK ozone generator cells use ozone core discharge of invention patent, including the integration design of ozone generator tube, ozone driving circuit and air pump, they can provide stable and efficient ozone output, easy to install and maintain.

Features:

- Increasing heat dissipation on the basis of FQ-300
- Integrated design three in one unit with driving circuit, ozone generator tube and air pump
- Stable & efficient output
- Low noise
- Long working life

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Washing machine, dishwasher, water machine, water purification machines, coin-operated sale water, fruit and vegetable detoxification machines, aquatic animals, the spa machine, surfing bathtub, slimmer.
- Medical apparatus and instruments, air purifier, disinfection cabinet, refrigerator, dryer, shoe ark, wardrobe, beauty equipment, oxygen machine, toilet, incubator, car.

Size View:

