

B-series Ozone Generator **FQM-B05H**



Ozone Output:	2-4g/hr@15Lpm Air; 5-8g/hr@3Lpm O2
Ozone Generating Method:	Corona Discharge
Electrical:	AC220V-AC110V, 120W
Ozone Output Connection:	Φ 6.5mm Stainless steel lock joint
Accessory:	Hose +Air stone (Optional)
Case:	Plastic+ Ceramic
Ozone Control:	50-100% Variable
Dimension(LxWxH):	165 * 210 * 100 mm
Installation Dimension(LxW):	5.6"*2.7"(142 *68 mm)
Net Weight:	- kg

BEYOK
百悦康☆☆☆☆

The FQM-B series of BEYOK ozone generator cells with ceramic discharge body are mainly used for air disinfections and sterilizations, they can provide stable and efficient ozone output, easy to install, operate and maintain.

Features:

- Long working life
- High efficiency
- Integrated design
- Overheat protection
- 50~100% variable ozone output control

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Mini air purification and disinfection equipment: medical equipment, incubator, air curtain, air condition, exhaust duct, workshop, hospital
- Mini water treatment equipment: swimming pool, landscape pool, waste yard

Size View:

