

Ozone Generator Cell **FQP-056**



BEYOK
OZONE

Ozone Output:	40-60 mg/hr @ air
Ozone Generating Method	Corona Discharge
Electrical:	AC220V-AC110V- DC12V-DC5V, 3W
Ozone Output Method:	Release into the air directly
Accessory:	None
Case:	Plastic
Circuit Dimension(LxWxH):	1.7"*0.9"*0.8"(42*24*21mm)
Dimension(LxW):	1.0"*0.4"(25*10 mm)
Installation Dimension:	1.9"(48 mm); Φ 0.2"(4 mm)
Net Weight:	- kg

The CQP series ozone generator cells with ceramic discharge body are mainly used for air disinfection and sterilization, they can provide stable and efficient ozone output, easy to install, operate and maintain.

Features:

- Widely used in large quantities
- Reliable quality
- Stable & efficient output
- Integrated design two in one unit with ozone ceramic and ozone power
- Using "high-frequency ceramic creeping discharge" generated ozone technology

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Disinfection cabinet, wardrobe, dryer, refrigerator, incubator, toilet.
- Medical equipment, air purifier, beauty equipment, car, air conditioning, ventilation, air curtain machine.

Size View:

