

### Ozone Generator Cell **FQT-100**



BEYOK OZONE

Ozone Output:	50-100 mg/hr @ air
External gas source:	1-5L/min@air; 0.5-2L/min@oxygen
Ozone Generating Method	Corona Discharge
Electrical:	AC220V-AC110V-AC24V-DC12V, 5W
Ozone Outlet Connection:	Φ 6mm pagoda joint
Case:	Plastic
Accessory:	Hose +Air stone (Optional)
Dimension(LxWxH):	2.5"*2.0"*1.4" (63*52*35 mm)
Installation Dimension(LxW):	2.5"*2.0"(75*40 mm)
Net Weight:	0.2lbs (0.1 kg)

The FQT-series of BEYOK ozone generator cells use ozone core discharge of invention patent including the integration design of ozone generator tube and ozone driving circuit (without air pump), they can provide stable and efficient ozone output, easy to install and maintain.

#### Features:

- Invention patent ZL200410079317.5
- Integrated design two in one unit with driving circuit and ozone generator tube
- Stable & efficient output
- Low noise
- Long working life

#### Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

#### Application:

- Washing machine, dishwasher, water machine, water purification machines, coin-operated sale water, fruit and vegetable detoxification machines, aquatic animals, the spa machine, surfing bathtub, slimmer.
- Medical apparatus and instruments, air purifier, disinfection cabinet, refrigerator, dryer, shoe ark, wardrobe, beauty equipment, oxygen machine, toilet, incubator, car.

#### Size View:

