

Ozone Generator Cell **FQT-300pro**



BEYOK
百悦康☆☆☆☆

Ozone Output:	300-500 mg/hr @ air
External gas source:	1-5L/min@air; 0.5-2L/min@oxygen
Ozone Generating Method	Corona Discharge
Electrical:	AC220V-AC110V-DC12V,9W
Ozone Outlet Connection:	Φ 7*4mm Silicone hose
Case:	Plastic
Accessory:	Hose +Air stone (Optional)
Dimension(LxWxH):	3.8"*3.3"*1.7"(97*83*42 mm)
Installation Dimension(LxW):	4.1"*1.6"(105*40 mm)
Net Weight:	- kg

The FQT-series of BEYOK ozone generator cells use ozone core discharge of invention patent including the integration design of ozone generator tube and ozone driving circuit (without air pump), they can provide stable and efficient ozone output, easy to install and maintain.

Features:

- On the basis of FQ-300F, add titanium material ozone tube and driving power supply
- Forced cooling
- Integrated design two in one unit with driving circuit and ozone generator tube
- Stable& efficient output
- Low noise
- Long working life

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Washing machine, dishwasher, water machine, water purification machines, coin-operated sale water, fruit and vegetable detoxification machines, aquatic animals, the spa machine, surfing bathtub, slimmer.
- Medical apparatus and instruments, air purifier, disinfection cabinet, refrigerator, dryer, shoe ark, wardrobe, beauty equipment, oxygen machine, toilet, incubator, car.

Size View:

