

Ozone Air Generator System **GQA-S50**



Ozone Output:	30-50 g/hr @ O ₂
Ozone Generating Method:	Corona Discharge
Electrical:	220V/50Hz-120V/60Hz, MAX 3500W
Air volume:	Air duct air volume
Control:	Manual/ PLC
Accessory:	Φ50mm Bellows
Application Range:	1500-3000 m ³
Case:	Carbon steel
Dimension(LxWxH):	35.6"*27.2" *59.1" (900*690*1500mm)
Net Weight:	- kg

The GQA-S series of BEYOK ozone air generator system product and discharge ozone to pipe by compressed fan, the system include oxygen generator. Ozone can destroy bacteria, purify air and eliminate peculiar smell. They are suitable for the places which always need to clean, such like poultry farms, flower farms, greenhouses, etc.

Features:

- Simple operation
- High efficiency
- Strong ventilation
- Good dispersion
- Easy to maintain
- Long working life

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Sterilization and disinfection: restaurant, hospital, packing workshop, food factory.
- Food fresh keeping: refrigerated storage.
- Deodorization: basement, garage, hotel.

Size View:

