

# Skid-mounted Ozone Generator GQO-A15 Ozone Output: 15 g/hr Ozone Generating Method: Corona Discharge Electrical: 220V/50Hz, 220W Gas Source Input: Built-in air pump / External oxygen Ozone concentration: 15-25mg/L / 60-120mg/L@4LpmO2 Timer Control: Programmable controller Ozone Control: 50-100% variable Apply to space: 50-100m<sup>2</sup> Cooling way: Air cooling Case: Stainless steel Dimension (L\*W\*H): 15.7"\*11.8"\*23.6" (400\*300\*600mm) Net weight: 15 kg

The GQO-A series of BEYOK skid-mounted ozone generators can mix ozone into water to destroy bacteria, purify air and eliminate peculiar smell. They are suitable for food factory assembly lines, restaurants, and refrigerated storages, etc. Connect to the external oxygen source will provide a higher concentration of ozone.

#### **Features:**

- · Skid-mounted
- · Compact design with built-in air pump
- · Simple operation
- · High efficiency
- High concentration
- Good dispersion
- · Easy to maintain
- · Long working life

### **Benefits:**

- High efficient broad-spectrum sterilization
- Good dispersion
- · Without ozone residual and secondary pollution

## **Application:**

- Sterilization and disinfection: restaurant, hospital, packing workshop, food factory.
- · Food fresh keeping: refrigerated storage.
- · Deodorization: basement, garage, store room, hotel.

## Size View:

