

Wall Mounted Ozone Generator **GQO-P07V**



BEYOK
百悦康☆☆☆☆

Ozone Output:	5-10 g/hr@20Lpm Air, air pump inside
Ozone Generating Method:	Corona Discharge
Electrical:	220V/50Hz-120V/60Hz, 100W
Pump Output	20 L/min, 20KPa
Control:	Programmable electronic loop controller
Cooling Method:	Air cooled
Inlet & Outlet Connection:	0.3"*0.2"(8*6mm) Stainless steel
Case:	Plastic
Dimension(LxWxH):	15.1" *7" *15.7" (384*177*400 mm)
Net Weight:	-lbs (- kg)
Adapted swimming pool:	100m3

The GQO-P-V series of BEYOK wall mounted ozone generators can mix ozone into water to destroy bacteria and eliminate peculiar smell. Connect to the external oxygen source will provide a higher concentration of ozone.

Features:

- Wall mounted
- Compact design and simple operation
- External oxygen or dry air feed
- High efficiency
- Work continuously
- Economical, and low running costs
- Long working life

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Disinfection: Swimming pool and small water treatment.
- Food fresh keeping: restaurant, refrigerated storage.
- Deodorization: basement, store room, hotel, central air-conditioning cooling tower.

Size View:

