

Wall Mounted Ozone Generator **GQO-P15V**



BEYOK
百悦康☆☆☆☆

Ozone Output:	20 g/hr@5Lpm O2 external
Ozone Generating Method:	Corona Discharge
Electrical:	220V/50Hz-120V/60Hz, 180W
Gas Source Input:	Connect to external gas source
Control:	Outside connect to system control board
Cooling Method:	Air cooled
Inlet & Outlet Connection:	0.3"*0.2"(8*6mm)Stainless steel
Case:	Metal
Dimension(LxWxH):	11.8" *6.7" *18.9" (300*170*480 mm)
Net Weight:	-lbs (- kg)
Adapted swimming pool:	300m3

The GQO-P-V series of BEYOK wall mounted ozone generators can mix ozone into water to destroy bacteria and eliminate peculiar smell. Connect to the external oxygen source will provide a higher concentration of ozone.

Features:

- Wall mounted
- Compact design and simple operation
- External oxygen or dry air feed
- High efficiency
- Work continuously
- Economical, and low running costs
- Long working life

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Disinfection: swimming pool and small water treatment.
- Food fresh keeping: restaurant, refrigerated storage.
- Deodorization: basement, store room, hotel, central air-conditioning cooling tower.

Size View:

