

Mobile Ozone Water System **GQW-M01**



Ozone Output:	10 g/h
Ozone Generating Method:	Corona Discharge
Electrical:	220V/50Hz, 800W
Feed gas:	Built-in oxygen source
Ozone concentration in water:	1-3 ppm
Treat water flow:	0.5-1.0 m3/h
Timer Control:	Programmable controller
Ozone Control:	50-100% variable
Water Connection:	3/4-in, 3/4-in
Case:	Stainless steel
Dimension (L*W*H):	31.5"*13.4"*38.3" (800*340*972mm)
Net weight:	60 kg

The GQW-M series of BEYOK mobile ozone water systems have perfect ozone production systems including oxygen source system, ozone system, gas-water mixing system, cooling system and automatic control system, can destroy bacteria, purify air and eliminate peculiar smell. They are suitable for large places which need to clean with ozone water directly like slaughter houses etc.

Features:

- Mobile
- Compact design
- Simple operation
- 50~100% variable ozone output control
- Gas-water mixing system
- Easy to maintain
- Long working life

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Sterilization and disinfection: canteen, hospital, swimming pool, slaughter house, water filling production line.
- Deodorization: hotel, central air-conditioning cooling tower

Size View:

