

### Industrial Ozone Water System **GQW-P03V**



**BEYOK**  
百悦康☆☆☆☆

Ozone Output:	3 g/hr@Injector air input
Ozone Generating Method:	Corona Discharge
Electrical:	220V/50Hz-120V/60Hz, 60W
Ozone Control:	no variable
Control:	Water flow controller
Water Processing Volume:	1-2mg/L@1-2TPH
Water Connection:	G3/4" Stainless steel screw
Case:	Stainless steel
Dimension(LxWxH):	10.2" *3.9" *13.4" (260*100*340 mm)
Net Weight:	-lbs (- kg)
Adapted swimming pool:	30m3

The GQW-P series of BEYOK industrial ozone water systems have perfect ozone production systems including oxygen source system, ozone system, gas-water mixing system, cooling system and automatic control system, can destroy bacteria, purify air and eliminate peculiar smell. They are suitable for swimming pool, large food processing plants, canteen, sewage treatment, etc.

#### Features:

- Wall mounted
- Compact design
- Simple operation
- Gas-water mixing system
- Easy to maintain
- Long working life

#### Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

#### Application:

- Disinfection: Swimming pool and small water treatment.
- Deodorization: basement, store room, hotel, central air-conditioning cooling tower.

#### Size View:



**GQW-P03V**