

Industrial Ozone Water System **GQW-P05M**



BEYOK
百悦康☆☆☆☆

Ozone Output:	5g/hr@Injector air input
Ozone Generating Method:	Corona Discharge
Electrical:	220V/50Hz-120V/60Hz,120W
Ozone Control	no variable
Control:	Timer controller
Water Processing Volume:	1-2mg/L@1-2TPH
Water Connection:	G1/2" Stainless steel screw
Case:	Stainless steel
Dimension(LxWxH):	13.4" *7.1" *7.1" (340*180*180 mm)
Net Weight:	-lbs (- kg)
Adapted swimming pool:	50m3

The GQW-P series of BEYOK industrial ozone water systems have perfect ozone production systems including oxygen source system, ozone system, gas-water mixing system, cooling system and automatic control system, can destroy bacteria, purify air and eliminate peculiar smell. They are suitable for swimming pool, large food processing plants, canteen, sewage treatment, etc.

Features:

- Portable
- Compact design
- Simple operation
- Gas-water mixing system
- Easy to maintain
- Long working life

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Disinfection: Swimming pool and small water treatment.
- Deodorization: basement, store room, hotel, central air-conditioning cooling tower.

Size View:

