

Mobile Ozone Water System **GQW-P20C**



Ozone Output:	20g/hr@5Lpm Built-in O2 system
Ozone Generating Method:	Corona Discharge
Electrical:	220V/50Hz-120V/60Hz, 1100W
Ozone Control:	50-100% variable
Control:	Programmable controller
Water Processing Volume:	2-4mg/L@1-2TPH
Water Connection:	G3/4" Stainless steel screw
Case:	Stainless steel
Dimension(LxWxH):	23.6" *13.8" *31.5" (600*350*800 mm)
Net Weight:	-lbs (- kg)
Adapted swimming pool:	200m3

The GQW-P series of BEYOK industrial ozone water systems have perfect ozone production systems including oxygen source system, ozone system, gas-water mixing system, cooling system and automatic control system, can destroy bacteria, purify air and eliminate peculiar smell. They are suitable for swimming pool, large food processing plants, canteen, sewage treatment, slaughter houses etc.

Features:

- Mobile
- Compact design
- Simple operation
- 50~100% variable ozone output control
- Gas-water mixing system
- Easy to maintain
- Long working life

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Disinfection: Swimming pool and small water treatment.
- Deodorization: basement, store room, hotel, central air-conditioning cooling tower.

Size View:

