

Industrial Ozone Water System **GQW-P50G**



BEYOK
百悦康☆☆☆☆

Ozone Output:	40-50g/hr@10Lpm Built-in O2 system
Ozone Generating Method:	Corona Discharge
Electrical:	220V/50Hz-120V/60Hz, 2400W
Ozone Control:	50-100% variable
Control:	Programmable controller
Water Processing Volume:	2-4mg/L@2-4TPH
Water Connection:	G3/4" Outlet; G1" Inlet
Case:	Stainless steel
Dimension(LxWxH):	19.7" *16.5" *35.4" (500*420*900 mm)
Net Weight:	-lbs (- kg)
Adapted swimming pool:	400m3

The GQW-P series of BEYOK industrial ozone water systems have perfect ozone production systems including oxygen source system, ozone system, gas-water mixing system, cooling system and automatic control system, can destroy bacteria, purify air and eliminate peculiar smell. They are suitable for swimming pool, large food processing plants, canteen, sewage treatment, slaughter houses etc.

Features:

- Floor standing
- Compact design
- Simple operation
- 50~100% variable ozone output control
- Gas-water mixing system
- Easy to maintain
- Long working life

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Disinfection: Swimming pool and small water treatment.
- Deodorization: basement, store room, hotel, central air-conditioning cooling tower.

Size View:

