

Industrial Ozone Water System **GQW-S01**



BEYOK
百悦康☆☆☆☆☆

| | |
|-------------------------------|---------------------------------------|
| Ozone Output: | 10 g/h |
| Ozone Generating Method: | Corona Discharge |
| Electrical: | 220V/50Hz, 800W |
| Feed gas: | Built-in oxygen source |
| Ozone concentration in water: | 1-3 ppm |
| Treat water flow: | 0.5-1.0 m3/h |
| Timer Control: | Programmable controller |
| Ozone Control: | 50-100% variable |
| Water Connection: | 3/4-in, 1/2-in |
| Case: | Stainless steel |
| Dimension (L*W*H): | 16.5"*13.8"*45.3" (420*350*1150mm) |
| Net weight: | 54 kg |

The GQW-S series of BEYOK industrial ozone water systems have perfect ozone production systems including oxygen source system, ozone system, gas-water mixing system, cooling system and automatic control system, can destroy bacteria, purify air and eliminate peculiar smell.

Features:

- Floor standing
- Compact design
- Simple operation
- 50~100% variable ozone output control
- Gas-water mixing system
- Easy to maintain
- Long working life

Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

Application:

- Sterilization and disinfection: canteen, hospital, swimming pool, slaughter house, water filling production line.
- Deodorization: hotel, central air-conditioning cooling tower

Size View:

