

### Industrial Ozone Water System **GQW-S02**



**BEYOK**  
百悦康☆☆☆☆☆

Ozone Output:	20 g/h
Ozone Generating Method:	Corona Discharge
Electrical:	220V/50Hz, 1200W
Feed gas:	Built-in oxygen source
Ozone concentration in water:	1-4 ppm
Treat water flow:	1.0-2.0 m3/h
Timer Control:	Programmable controller
Ozone Control:	50-100% variable
Water Connection:	1-in, 3/4-in
Case:	Stainless steel
Dimension (L*W*H):	16.5"*13.8"*45.3" (420*350*1150mm)
Net weight:	65 kg

The GQW-S series of BEYOK industrial ozone water systems have perfect ozone production systems including oxygen source system, ozone system, gas-water mixing system, cooling system and automatic control system, can destroy bacteria, purify air and eliminate peculiar smell.

#### Features:

- Floor standing
- Compact design
- Simple operation
- 50~100% variable ozone output control
- Gas-water mixing system
- Easy to maintain
- Long working life

#### Benefits:

- High efficient broad-spectrum sterilization
- Good dispersion
- Without ozone residual and secondary pollution

#### Application:

- Sterilization and disinfection: canteen, hospital, swimming pool, slaughter house, water filling production line.
- Deodorization: hotel, central air-conditioning cooling tower

#### Size View:

