

Ozone Injector **HH-P40**



BEYOK
百悦康☆☆☆☆☆

| | |
|-------------------|---------------------------------|
| Body Material: | PVDF+PVC |
| Water Flow: | 3-6 CMH |
| Water Pressure: | 0.3-0.6 MPa |
| Air Flow: | 6-12 LPM |
| Water Connection: | (DN50) 2.0-in Pipes |
| Suction Port: | (12mm) 0.5-in Barb + 1/2-in NPT |
| Check Valve: | Included - in the suction port |
| Supply Water : | Temp. 0-60°C, PH value 5-11 |
| Body Length: | 26.5" (672 mm) |
| Net Weight: | 2.6 lb (1.2 kg) |

The HH- series ozone venturi injectors of BEYOK are designed to be used with an ozone generator for water treatment. It is excellent for ozone mass transfer. Molded PVDF & rugged construction ensure its lifetime. Ozone suction port quickly transfers ozone gas into water stream under pressure. The HH-series include PVC, PC, stainless steel and other materials to meet different usage requirements. The caliber ranges DN08-DN125, and the water flow rate ranges 0.1-50t/h, which can be used in various ozone gas water mixing situations.

Features:

- No moving parts
- Durable PVDF+PVC pipes construction
- Completely ozone compatible
- Check valve included in injection port
- Quick installation

Applications:

- Ozone to water mixing
- Air to water mixing

Product series:

| Model | Material | Water Flow | Air Flow | Water Connection | Suction Port | Length |
|--------|----------|------------|-----------|---------------------|---------------------------------|----------------|
| HH-P25 | PVDF+PVC | 1-3 CMH | 2-6 LPM | (DN32) 1.2-in Pipes | (8mm) 0.3-in Barb + 1/2-in NPT | 19.5" (495 mm) |
| HH-P40 | PVDF+PVC | 3-6 CMH | 6-12 LPM | (DN50) 2.0-in Pipes | (12mm) 0.5-in Barb + 1/2-in NPT | 26.5" (672 mm) |
| HH-P50 | PVDF+PVC | 6-10 CMH | 12-20 LPM | (DN65) 2.5-in Pipes | (12mm) 0.5-in Barb + 1/2-in NPT | 34.3" (872 mm) |

Size View:

