

Ozone Injector HH-S125



BEYOK
百悦康☆☆☆☆☆

Body Material:	Stainless Steel
Water Flow:	30-50 CMH
Water Pressure:	0.5-1.0 MPa
Air Flow:	60-100 LPM
Water Connection:	(DN125) 5-in Flange
Suction Port:	(DN50) 2.0-in Flange
Check Valve:	-
Supply Water :	Temp. 0-60°C, PH value 5-11
Body Length:	33.9-in (860 mm)
Net Weight:	-lb (kg)

The HH- series ozone venturi injectors of BEYOK are designed to be used with an ozone generator for water treatment. It is excellent for ozone mass transfer. Molded PVDF & rugged construction ensure its lifetime. Ozone suction port quickly transfers ozone gas into water stream under pressure. The HH-series include PVC, PC, stainless steel and other materials to meet different usage requirements. The caliber ranges DN08-DN125, and the water flow rate ranges 0.1-50t/h, which can be used in various ozone gas water mixing situations.

Features:

- No moving parts
- Durable Stainless Steel construction
- Completely ozone compatible
- Check valve included in injection port
- Quick installation

Applications:

- Ozone to water mixing
- Air to water mixing

Product series:

Model	Material	Water Flow	Air Flow	Water Connection	Suction Port	Length
HH-S80	Stainless Steel	10-20 CMH	20-40 LPM	(DN80) 3-in Flange	(DN40) 1.5-in Flange	20.5-in (520 mm)
HH-S100	Stainless Steel	20-40 CMH	40-80 LPM	(DN100) 4-in Flange	(DN50) 1.5-in Flange	27.2-in (690 mm)
HH-S125	Stainless Steel	30-50 CMH	60-100 LPM	(DN125) 5-in Flange	(DN50) 2.0-in Flange	33.9-in (860 mm)

Size View:

