


Ozone Injector HH-U15P



BEYOK
百悦康☆☆☆☆☆

Body Material:	PVC
Water Flow:	0.2-0.5 CMH
Water Pressure:	0.1-0.3 MPa
Air Flow:	0.4-1.0 LPM
Water Connection:	(DN15) 1/2-in Pipes
Suction Port:	(7mm) 0.3-in Barb +1/4-in NPT
Check Valve:	Included - in the suction port
Supply Water :	Temp. 0-60°C, PH value 5-11
Body Length:	5.8-in (147 mm)
Net Weight:	-lb (kg)

The HH- series ozone venturi injectors of BEYOK are designed to be used with an ozone generator for water treatment. It is excellent for ozone mass transfer. Molded PVDF & rugged construction ensure its lifetime. Ozone suction port quickly transfers ozone gas into water stream under pressure. The HH-series include PVC, PC, stainless steel and other materials to meet different usage requirements. The caliber ranges DN08-DN125, and the water flow rate ranges 0.1-50t/h, which can be used in various ozone gas water mixing situations.

Features:

- No moving parts
- Durable PVC/UPVC construction
- Completely ozone compatible
- Check valve included in injection port
- Quick installation

Applications:

- Ozone to water mixing
- Air to water mixing

Product series:

Model	Material	Water Flow	Air Flow	Water Connection	Suction Port	Length
HH-C15	PC	0.2-0.4 CMH	0.2-0.5 LPM	(DN15) 1/2-in NPT	(4mm) 0.2-in Barb	3.5-in (89 mm)
HH-U15N	PVC	0.2-0.5 CMH	0.4-1.0 LPM	(DN15) 1/2-in NPT	(7mm) 0.3-in Barb+1/4-in NPT	5.6-in (142 mm)
HH-U15B	PP	0.2-0.5 CMH	0.4-1.0 LPM	(22mm) 0.8-in Barb	(7mm) 0.3-in Barb+1/4-in NPT	5.9-in (150 mm)
HH-U15P	PVC	0.2-0.5 CMH	0.4-1.0 LPM	(20mm) 1/2-in Pipes	(7mm) 0.3-in Barb+1/4-in NPT	5.8-in (147 mm)

Size View:

